

V-SERIES OPTIONS



The V-Series consists of robust, reliable and user-friendly high capacity ovens. They are manufactured for professional users, with high standards for baking quality, efficiency and low total costs.

The V-Series is a flexible range of ovens with different options and settings to suit bakeries which create different types of goods in major volumes.



V-SERIES OPTIONS

- 1. Rotating platform**
Makes it possible to use the majority of racks. Made of stainless steel.
- 2. Automatic rack lifting**
Motor driven hook that lifts the racks from the oven floor, making loading and unloading easier. This option means that the rack does not need to be lifted up onto a ramp or hook. The rack is placed on the floor, after which it is lifted and begins to rotate. Once baking is complete, the rack is automatically lowered to the floor of the oven so that it can be easily removed.
- 3. Canopy**
A large, solid canopy made of stainless steel. Effectively catches steam and heat when the oven door is opened. With exhaust fan for even better steam removal.
- 4. Insulated floor**
Reduces heat leakage to the floor underneath.
- 5. Large double glazed window in insulated door**
Easier monitoring of the baking process but less energy efficient.
- 6. Left-hand hinged insulated door with double glazed window, spring loaded door hinge and door stop**
The oven is supplied with a right-hand door as standard.
- 7. Automatic evacuation system (AES)**
An evacuation system that improves the working environment and safety in the bakery, as a fan is activated and vents hot air and steam when the door is opened.
- 8. Frequency converter for fans - Variable speed**
The fan speed is driven by a frequency converter to maintain the desired flow of air. Helpful when baking sensitive products such as meringues, macaroons and muffins.
- 9. Fully assembled oven**
The oven is delivered fully assembled, reducing installation and start-up time.
- 10. Sveba Connect Cloud Solution**
A cloud service solution that allows complete control of baking 24/7, from any hardware and any location in the world.

Dimensions

V30

Width: 1810 mm
Height: 2425 mm
Depth: 1450 mm
Depth with canopy: 2150 mm

V31/32

Width: 1915 mm
Height: 2425 mm
Depth: 1450 mm
Depth with canopy: 2150 mm

V40/41/42

Width: 2165 mm
Height: 2425 mm
Depth: 1700 mm
Depth with canopy: 2400 mm

V50/51/52

Width: 2490 mm
Height: 2425 mm
Depth: 1975 mm
Depth with canopy: 2675 mm

	V30	V31	V32	V40	V41	V42	V50	V51	V52
Suspension hook	●	●	●	●	●	●			
Automatic rack lifting device, max 350 kg	○	○	○						
Automatic rack lifting device, max 450 kg				○	○	○			
Rotating platform, max 600 kg	○	○	○	○	○	○			
Heavy duty rotating platform, max 800 kg				○	○	○	●	●	●

● Standard ○ Options

www.sveba.com